SENSORS AND ACTUATORS A VOLUMES A37–A38, JUNE–AUGUST 1993

Contents

Physical Sensors Plenary Lectures

Sensors in Europe and 'Eurosensors': state-of-the-art and the science in 1992. 1
W. Göpel (Tübingen, Germany)

Quo vadis smart sensors? 6
J. E. Brignell (Southampton, UK)

Technology

Scanning microsensors for nanotechnology. 11
M. Stedman (Teddington, UK)

A smart balanced thermal pyranometer using a sigma-delta A-to-D converter for direct communication with micro-controllers 16
F. R. Riedijk and J. H. Huijsing (Delft, Netherlands)

High temperature silicon Hall sensor 26
S. R. in 't Hout and S. Middelhoek

A high sensitivity CMOS gas flow sensor on a thin dielectric membrane 33
D. Moser and H. Baltes (Zurich, Switzerland)

Thermal base drive for micromechanical resonators employing deep-diffusion bases 38
S. Bouwstra, J. van Rooijen, H. A. C. Tilmans (Enschede, Netherlands), A. Selvakumar and K. Najafi (Ann Arbor, MI, USA)

Micro-liquid flow sensor 45
T. S. J. Lammerink, N. R. Tas, M. Elwenspoek and J. H. J. Fluitman (Enschede, Netherlands)

CMOS as sensor technology 51
H. Baltes (Zurich, Switzerland)

Mechanical and electrical properties of SiO_2 thin films r.f. sputtered on non-silicon substrates for mechanical sensors 57
A. García-Alonso, J. Artázcoz, E. Castaño, I. Obieta and F. J. Gracia (San Sebastián, Spain)

Anodic bonding of silicon to silicon wafers coated with aluminium, silicon oxide, polysilicon or silicon nitride 61
M. Nese and A. Hanneborg (Oslo, Norway)

Relation between electrical conductivity and structural characteristics in boron-doped LPCVD polycrystalline silicon used in sensor devices 68
S. Marco, O. Ruiz, J. Samitier, J. R. Morante (Barcelona, Spain) and J. Bausells (Bellaterra (Barcelona), Spain)

Capillary fill encapsulation of ISFETs. 74
J. E. A. Shaw (Hayes, UK)

Multi-purpose interface for sensor systems fabricated by CMOS technology with post-processing 77
C. Azeredo Leme and H. Baltes (Zurich, Switzerland)

High accuracy pressure measurement with a silicon resonant sensor 82
J. Greenwood and T. Wray (Groby, UK)

A composite membrane movement detector with dedicated interface electronics for animal activity tracking 86
S. Vergote, M. De Cooman, P. Wouters and B. Puers (Heverlee, Belgium)

Physical Sensors

Capacitive sensors: when and how to use them 93
R. Puers (Heverlee, Belgium)

Fabrication of piezoelectric thick-film low-voltage multilayer actuators using a new double-paste printing technique 106
H. Moilanen, S. Leppävuori and A. Uusimäki (Oulu, Finland)

Feasiblity of capacitive pressure sensors without compensation circuits. 112
P. Pons, G. Blasquez and R. Behocaray (Toulouse, France)

Elsevier Sequoia

Gyrometer application for a low-frequency active suspension 116
J. P. Colinot, V. Hernette and Ph. Jarri (Vélizy, France)

Non-contact sensors for road conditions 121
F. Holzwarth (Stuttgart, Germany) and U. Eichhorn (Darmstadt, Germany)

Advances in sensors for aerospace applications 128
S. J. Prosser (Solihull, UK)

Ultrasound gas-flow meter for household application. 135
A. von Jena, V. Mágori (Munich, Germany) and W. Russwurm (Nürnberg, Germany)

Acoustic sensors based on surface-localized HPSWs for measurements in liquids. 141
H. Drobe, A. Leidl, M. Rost and I. Ruge (Munich, Germany)

Polaroid-effect rotor-position sensor for an autopiloted motor application. 149
A. L. Rodrigues (Caparica, Portugal)

Determination of characteristic magnetotransistor parameters by measurement and inverse modelling 158
G. Wachutka, C. Riccobene, R. Castagnetti and H. Baltes (Zurich, Switzerland)

Design and investigation of micromechanical bridge structures for an optical pressure sensor with temperature compensation 167
H. Bartelt and H. Unzeitig (Erlangen, Germany)

Optical Sensors

Infrared sensing and analysis in industrial measurements 173
J. Lammasniemi and T. Hyvärinen (Oulu, Finland)

An extended-range fibre-optic pH sensor. 180
F. Baldini, S. Bracci and F. Cosi (Florence, Italy)

New 'in-line' optical-fibre sensor based on surface plasmon excitation 187
R. Alonso, F. Villuendas, J. Tornos and J. Pelayo (Zaragoza, Spain)

Optical torque sensor for automotive steering systems. 193
R. J. Hazelden (Solihull, UK)

Optimization of a turning passive IR watching detector. 198
D. Esteve (Toulouse, France), L. Audaire (Grenoble, France), F. Bauer (Saint-Louis, France), J.-P. Beconne, J. Clot, A. Mahrane, V. V. Pham and J. J. Simonne (Toulouse, France)

A review of optical actuators and the impact of micromachining. 202
B. E. Jones and J. S. McKenzie (Uxbridge, UK)

Development of optical speed-over-ground sensors 208
I. Sakai, N. J. Chilton, S. J. Pacaud and R. J. Hazelden (Solihull, UK)

Thermoelectric infrared sensors in CMOS technology 216
R. Lenggenhager, H. Baltes and T. Elbel (Zurich, Switzerland)

Industrial process sensor based on surface plasmon resonance (SPR)
1. Distillation process monitoring. 221
E. García Ruiz, I. Garcés, C. Aldea, M. A. López, J. Mateo (Zaragoza, Spain), J. Alonso-Charmarro and S. Alegret (Bellaterra (Barcelona), Spain)

A silicon-diode-based infrared thermal detector array 226
Y.-P. Xu, R.-S. Huang and G. A. Rigby (Kensington, NSW, Australia)

Sensorial Systems

Sensors and systems in space: Ariane 5 233
M. Trojaola (Aretxabaleta, Guipuzcoa, Spain)

Smart sensors in flexible manufacturing systems 239
M. Robert, J. M. Rivière, J. L. Noizette and F. Hermann (Vandoeuvre, France)

Interoperability of sensors and distributed systems 247
Y. Benkhellat, M. Siebert and J.-P. Thomesse (Vandoeuvre-lès-Nancy, France)

Genetic processing of the sensorial information 255
D. del Castillo Sobrino, J. Gasós Casao and C. García-Alegre Sánchez (Madrid, Spain)

A low power multi-channel sensor interface for use in digital telemetry 260
B. Puers, P. Wouters and M. De Cooman (Heverlee, Belgium)

Tactile sensing data interpretation for object manipulation 268
D. Reynaerts and H. Van Brussel (Heverlee, Belgium)

Marketing and design in flow sensing 274
W. Jouwsma (Ruurlo, Netherlands)

Adaptive filters in load cell response correction 280
W. J. Shi, N. M. White and J. E. Brignell (Southampton, UK)

Selectivity of sensor systems 286
L. Zipser (Dresden, Germany)

A pyroelectric matrix sensor using PVDF on silicon containing FET readout circuitry 290
P. C. A. Hammes, P. P. L. Regtien and P. M. Sarro (Delft, Netherlands)

Resolution of sensor array: noise considerations and design implications 296
F. A. M. Davide (L'Aquila, Italy), C. Di Natale and A. D'Amico (Rome, Italy)

A transducer for the measurement of forces in external fracture fixator devices: test results 301
J. Viñolas, J. R. Añorga (San Sebastián, Spain), F. Forriol (Pamplona, Spain) and I. Goenaga (San Sebastián, Spain)

POSTERS

Physical Sensors

Using the quartz microbalance principle for sensing mass changes and damping properties 309
P. Hauptmann, R. Lucklum, J. Hartmann, J. Auge (Magdeburg, Germany) and B. Adler (Schkopau, Germany)

Analysis of electrostatic-damped piezoresistive silicon accelerometers 317
S. Marco, J. Samitier, O. Ruiz, A. Herms and J. R. Morante (Barcelona, Spain)

The use of depolarized Rayleigh scattering for measurement applications in process industry 323
A. P. Toropainen (Espoo, Finland)

High-temperature thin-film strain gauges 328
P. Kayser, J. C. Godefroy and L. Leca (Châtillon, France)

Plasma-deposited silicon nitride films with low hydrogen content for amorphous silicon thin-film transistors application 333
J. Campmany, J. L. Andújar, A. Canillas, J. Cifre and E. Bertran (Barcelona, Spain)

A thick-film resonant sensor for humidity measurements 337
B. Morten, G. De Cicco and M. Prudenziati (Modena, Italy)

Polymer/ceramic composites for piezoelectric sensors 343
C. Dias, D. K. Das-Gupta (Bangor, UK), Y. Hinton and R. J. Shuford (Watertown, MA, USA)

A novel accelerometer using thick-film technology 348
R. P. Sion, J. K. Atkinson and J. D. Turner (Southampton, UK)

A study of CuPC/water interactions using surface acoustic wave devices 352
D. Rebiere, J. Pistre (Talence, France), M. Hoummady, D. Hauden (Besançon, France) and R. Planade (Vert-Le-Petit, France)

Piezoresistive simulation in MOSFETs 357
Z. Z. Wang (Lille, France), J. Suski (Montrouge, France) and D. Collard (Lille, France)

P(VDF/TrFE) copolymer films for the fabrication of pyroelectric arrays 365
W. von Münch, M. Nägele, M. Rinner, G. Wöhl (Stuttgart, Germany), B. Ploss and W. Ruppel (Karlsruhe, Germany)

The effect of gate-oxide process variations on the long-term fading of PMOS dosimeters 370
A. Kelleher, N. McDonnell, B. O'Neill, W. Lane (Cork, Ireland) and L. Adams (Noordwijk, Netherlands)

Piezoelectric and thermoelectric response of cuprous oxide, Cu_2O 375
V. Chang, H. Rojas and J. Jorge (Caracas, Venezuela)

Acoustic Sensors

A piezoelectric range sensor for thickness measurements in refractory materials 381
A. S. Fiorillo, N. Lamberti and M. Pappalardo (Fisciano (SA), Italy)

A 5 MHz high-voltage demultiplexed ultrasonic array system for rapid-scan testing of advanced materials 385
A. Ramos, F. R. Montero de Espinosa, P. T. Sanz and J. M. Torregrosa (Madrid, Spain)

A three-transducer ultrasonic system for object location in air 391
L. G. Ullate, M. T. Sanchez, E. Villanueva, M. Parrilla and J. J. Anaya (Madrid, Spain)

An acoustic transducer system for long-distance ranging applications in air. 397
J. A. Gallego-Juárez, G. Rodriguez, J. L. San Emeterio, P. T. Sanz and J. C. Lázaro (Madrid, Spain)

Development of an ultrasonic transducer using long acoustic waves for flow measurement 403
E. S. Ikpe, G. G. Scarrott, J. P. Weight and K. T. V. Grattan (London, UK)

Ultrasonic detectors for high-intensity acoustic fields. 410
L. Gaete-Garretón, Y. Vargas-Hernández, S. Pino-Dubreuil (Santiago, Chile) and F. Montoya-Vitini (Madrid, Spain)

Magnetic Sensors

Race-track fluxgate sensors 417
P. Ripka (Prague, Czech Republic)

Magnetoresistive force sensors for use in an instrumented pen. 422
R. T. Rakowski, L. F. Borjon-Figueroa and B. E. Jones (Uxbridge, UK)

Design of a balance sensor for automotive application 430
A. Z. Liu, I. Z. Rahman and M. A. Rahman (Limerick, Ireland)

Analog magnetic and digital transducers of mechanical displacements 435
G. Ferraris (Robbiate (CO), Italy)

Magnetometric sensor to control the ground traffic of aircraft 442
B. Tamayo, F. Sempere, M. Hernandez, C. Aroca, E. Lopez, M. C. Sanchez and P. Sanchez (Madrid, Spain)

Flicker noise and offset suppression in symmetric Hall plates. 449
Z. Stoessel (Zug, Switzerland) and M. Resch (Stockholm, Sweden)

Analysis and performance of a shear-wave magnetometer 453
C. F. Kilby, P. T. Squire (Bath, UK) and S. N. M. Willcock (Hayes, UK)

Non-contact amorphous speed sensor 458
T. Meydan and B. M. F. Bushofa (Cardiff, UK)

Current measurements based on thin-film magnetoresistive sensors 461
W. Andrä, S. Kühn and P. Pertsch (Jena, Germany)

A novel highly sensitive magnetic sensor. 466
U. Barjenbruch (Kassel, Germany)

Optical Fiber Sensors

A fibre-optic 3-D analog probe for component scanning on coordinate-measuring machines 473
C. Butler and Q. Yang (Uxbridge, UK)

An optical-fibre hybrid pressure transducer employing a mechanical resonator 480
J. A. Lethbridge, A. Cheshmehdoost, C. M. France and B. E. Jones (Uxbridge, UK)

Fiber- and integrated-optical microphones based on intensity modulation by beam deflection at a moving membrane 484
D. Garthe (Darmstadt, Germany)

Acoustic-field fibre-optic sensor 489
A. Paternottre, F. Molpeceres, F. R. Montero de Espinosa, R. Carbó, F. J. Chinchurreta and M. A. Muriel (Madrid, Spain)

Infrared and Radiation Sensors

Thin metal films as absorbers for infrared sensors 497
S. Bauer, S. Bauer-Gogonea, W. Becker, R. Fettig, B. Ploss, W. Ruppel (Karlsruhe, Germany) and W. von Münch (Stuttgart, Germany)

Multispectral interference filters and their application to the design of compact non-dispersive infrared gas analysers for pollution control 502
F. López and J. de Frutos (Madrid, Spain)

Thin-film semiconductor electrodes deposited on pyroelectric ceramics: application to compact spectrally selective pyroelectric IR sensors 507
J. de Frutos and F. López (Madrid, Spain)

Monolithically integrated LED, waveguide and photodetector optical system for near-infrared biosensor 512
P. Huertas, G. Mier, M. L. Dotor, J. V. Anguita, D. Golmayo and F. Briones (Madrid, Spain)

Improvement of lead titanate ceramic for infrared detectors 516
J. Mendiola, C. Alemany and J. de Frutos (Madrid, Spain)

Optical Semiconductor Devices

Thin-film electrooptical property study for FIR absolute radiometers 521
L. Brunetti (Turin, Italy)

Light-emitting devices in industrial CMOS technology 527
J. Kramer, P. Seitz, E. F. Steigmeier, H. Auderset, B. Delley and H. Baltes (Zurich, Switzerland)

A fail-safe sensor for flame detection 534
F. Riedel and Z. Stössel (Zug, Switzerland)

Novel optical fibre/microresonator interfacing technology 540
A. J. Jacobs-Cook and M. E. C. Bowen (Solihull, UK)

A lensless contact-type image sensor based on a CdSe photoconductive array 546
J. Capon, J. De Baets, I. De Rycke, H. De Smet, J. Doutreloigne, A. Van Calster and J. Vanfleteren (Ghent, Belgium)

Optical Sensors

Determination of low-voltage actuator displacements in d.c. and a.c. electric fields using an optical interferometer 555
H. Moilanen and S. Leppävuori (Oulu, Finaland)

Automatic optical sensor for thickness control of thin tramsparent films 561
A. González-Cano and E. Bernabéu (Madrid, Spain)

Application of integrated thick-film thermocouples for a laser power detector 565
W. Smetana and J. Nicolics (Vienna, Austria)

An optical current comparator for absolute current measurement 571
B. C. B. Chu, Y. N. Ning and D. A. Jackson (Canterbury, UK)

Detection of displacements in the nanometre range by optical tunnelling 577
A. Diaspro (Genoa, Italy), M. Aguilar (Madrid, Spain) and B. Bianco (Genoa, Italy)

Surface plasmon resonance sensor as a detector in HPLC and specific lactate determination 582
J. R. Castillo, G. Cepriá, S. de Marcos, J. Galbán, J. Mateo and E. García Ruiz (Zaragoza, Spain)

Sensorial Systems

Experimental comparison of sensors for tool-wear monitoring on milling 589
L. J. Barrios, A. Ruiz, D. Guinea, A. Ibañez, P. Bustos (Madrid, Spain) and J. Etxeberria (Eibar Guipuzcoa, Spain)

BiCMOS integrated circuit for capacitive pressure sensors in automotive applications 596
Ph. Dondon, Ch. Zardini and J. L. Aucouturier (Talence, France)

D-flip-flop with a programmable delay with power consumption for implementation in smart sensors 600
M. J. Rutka and R. F. Wolffenbuttel (Delft, Netherlands)

Evaluation of a mathematical model to simulate dynamic response of tubular potentiometric sensors in flow-injection systems 607
J. de Gracia, J. L. Montesinos, M. Poch, J. Alonso, J. Bartrolí (Bellaterra (Barcelona), Spain), I. M. P. L. V. O. Ferreira and J. L. F. C. Lima (Porto, Portugal)

Redundancy in sensor arrays 612
C. Di Natale, A. D'Amico (Rome, Italy) and F. A. M. Davide (L'Aquila, Italy)

Infrared sensor for suspended solids measurement in the activated sludge process 618
A. Urrutikoetxea, J. L. García-Heras (San Sebastián, Spain) and J. Gregory (London, UK)

A new electronic switch controlled by an infrared sensor 627
C. Amuchastegui, F. Arizti, J. J. Sánchez, J. M. Pérez Toca and F. J. Gracia (San Sebastián, Spain)

Robotic Sensors

Environment recognition in welding processes by ultrasonic sensors 635
R. Ceres, J. M. Martín, L. Calderón, T. Freire Bastos and M. Armada (Madrid, Spain)

Ultrasonic echoes from different orientations
Finding the normal inclination 639
J. M. Martín Abreu, L. Calderón, R. Ceres and T. Freire Bastos (Madrid, Spain)

A high-resolution object recognition ultrasonic system 644
C. Fritsch, J. J. Anaya, A. Ruiz and L. G. Ullate (Madrid, Spain)

Investigation of force and moment measurement system for a robotic assembly hand 651
M. Sorli (Turin, Italy) and N. Zhmud' (Riga, Latvia)

Microdevices Technology

Monolithic microbridges in silicon using laser machining and anisotropic etching 661
M. Alavi, Th. Fabula, A. Schumacher and H.-J. Wagner (Villingen-Schwenningen, Germany)

A monolithically-integrated transistor microphone: modelling and theoretical behaviour 666
R. Schellin and R. Mohr (Darmstadt, Germany)

An integrated sensor for invasive blood-velocity measurement 674
R. Kersjes, J. Eichholz, A. Langerbein, Y. Manoli and W. Mokwa (Duisburg, Germany)

GaAs Hall sensors suitable for domestic energy meter application 679
R. Campesato, C. Flores (Segrate, Italy), P. Mirandola and F. Veroni (Cologno Monzese, Italy)

A silicon microvalve with combined electromagnetic/electrostatic actuation 684
D. Bosch, B. Heimhofer, G. Mück, H. Seidel, U. Thumser and W. Welser (Munich, Germany)

A liquid velocity sensor based on the hot-wire principle 693
A. J. van der Wiel, C. Linder, N. F. de Rooij (Neuchâtel, Switzerland) and A. Bezinge (Bevaix, Switzerland)

Dual collector magnetotransistors with on-chip bias and signal-conditioning circuitry 698
R. Castagnetti, C. Azeredo Leme and H. Baltes (Zurich, Switzerland)

An optimized preparation process of stainless-steel substrates and their application to thin-film high pressure sensors 703
A. García-Alonso, X. Huizti, E. Castaño, I. Obieta and F. J. Gracia (San Sebastián, Spain)

Silicon membrane condenser microphone with integrated field-effect transistor 708
E. Graf, W. Kronast, S. Dühring, B. Müller and A. Stoffel (Furtwangen, Germany)

Micromachining

Measuring profile and position by means of vibrating quartz resonators used as tactile and nontactile sensors 715
M. Weinmann, R. Radius, F. Assmus and W. Engelhardt (Stuttgart, Germany)

Stress in low pressure chemical vapour deposition polycrystalline silicon thin films deposited below 0.1 Torr 723
A. Benitez, J. Bausells, E. Cabruja, J. Esteve (Bellaterra (Barcelona), Spain) and J. Samitier (Barcelona, Spain)

Etching front control of ⟨110⟩ strips for corner compensation 727
M. Bao, Chr. Burrer, J. Esteve, J. Bausells and S. Marco (Bellaterra (Barcelona), Spain)

Effects of r.f. power on optical and electrical properties of plasma-deposited hydrogenated amorphous silicon thin films 733
J. L. Andújar, J. Kasaneva, J. Serra, A. Canillas, C. Roch, J. L. Morenza and E. Bertran (Barcelona, Spain)

TMAH/IPA anisotropic etching cahracteristics 737
A. Merlos, M. Acero, M. H. Bao, J. Bausells and J. Esteve (Bellaterra (Barcelona), Spain)

Passivation analysis of micromechanical silicon structures obtained by electrochemical etch stop 744
A. Götz, J. Esteve, J. Bausells (Bellaterra (Barcelona), Spain), S. Marco, J. Samitier and J. R. Morante (Barcelona, Spain)

A new microstructured silicon substrate for ultrathin gas-sensitive films 751
A. Schütze, U. Weber, J. Zacheja, D. Kohl (Giessen, Germany), W. Mokwa, M. Rospert and J. Werno (Duisburg, Germany)

Comparison of techniques for measuring both compressive and tensile stress in thin films 756
B. P. van Drieënhuizen, J. F. L. Goosen, P. J. French and R. F. Wolffenbuttel (Delft, Netherlands)

Deep trenches in silicon using photoresist as a mask 766
E. Cabruja (Bellaterra (Barcelona), Spain) and M. Schreiner (Munich, Germany)

A measurement system for the visual analysis of integrated micromechanical devices 772
G. de Graaf, M. R. Wolffenbuttel and R. F. Wolffenbuttel (Delft, Netherlands)

CHF_3-reactive ion etching for waveguides 779
C. Dominguez, J. Muñoz (Bellaterra (Barcelona), Spain), R. Gonzalez and M. Tudanca (Torrejon de Ardoz (Madrid), Spain)

Strain sensitivity and temperature influence on sputtered thin films for piezoresistive sensors 784
A. García-Alonso, J. García, E. Castaño, I. Obieta and F. J. Gracia (San Sebastián, Spain)

Analysis of nonlinearity in high sensitivity piezoresistive pressure sensors 790
S. Marco, J. Samitier, O. Ruiz and J. R. Morante (Barcelona, Spain) and J. Esteve (Bellaterra (Barcelona), Spain)

Some studies of molecularly-imprinted polymer membranes in combination with field-effect devices 796
E. Hedborg, F. Winquist, I. Lundström (Linköping, Sweden), L. I. Andersson and K. Mosbach (Lund, Sweden)

Realization of mechanical decoupling zones for package-stress reduction 800
V. L. Spiering, S. Bouwstra and J. H. J. Fluitman (Enschede, Netherlands)

Author Index of Volumes A37 and A38 805

Subject Index of Volumes A37 and A38 807